

## Auto-Change Bag on Roll Making Machine with Paper Core Device Servo Shuttle system (in-line extruder possibility)



Multi-Line Auto Change  
Rewind Machine  
(Core winding System)

Shuttle System Sealing  
and Perforation Machine



### SPECIFICATION :

	Model 型號	Bag Width(mm) Roll Dia. (mm) 袋寬/ 卷徑	Bag Length/ Film thickness 袋長/膜厚 (mm)	Capacity 產能 (Meter /min)	Servo power / Servo quantity 伺服馬力/數量	Heater 電熱	Power Required 全台備電容量	Air supply Required 空壓需求	Machine Size 機器尺寸 LxWxH(M)	Packing Size 裝箱尺寸 LxWxH(M)	N.W. / G.W. 淨重 / 毛重 (Kgs)
OFF-LINE TYPE	STR-750S -A21E	W 300~750 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	11KW/ 6 Servo	M3.5 kw	13.5KW	0.6 Mpa 400ml / min	6.8x2.61x1.7	R-1.6x2.7x1.7 M-2.0x1.8x1.5 U-1.7x1.4x1.5	4400 / 5300
	STR-1000S -A21E	W 450~1000 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	12.5KW/ 6 Servo	M4.0 kw	15.5KW	0.6 Mpa 400ml / min	6.8x2.86x1.7	R-1.6x2.9x1.7 M-2.0x2.0x1.5 U-1.7x1.6x1.5	4900 / 6000
	STR-1250S -A21E	W 600~1250 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	12.5KW/ 6 Servo	M4.5 kw	16.0KW	0.6 Mpa 400ml / min	6.8x3.06x1.7	R-1.6x3.1x1.7 M-2.0x2.2x1.5 U-1.7x1.6x1.5	5700 / 7000
	STR-1500S -A21E	W 700~1500 Roll max.220	220~2500 / 0.010~0.12	Max. 90M/ line/ minute	13.5KW/ 6 Servo	M5.0 kw	17.5KW	0.6 Mpa 400ml / min	6.8x3.31x1.7	R-1.6x3.4x1.7 M-2.0x2.6x1.5 U-1.7x2.2x1.5	6300 / 7800
	STR-1750S -A21E	W 850~1700 Roll max.220	220~2500 / 0.012~0.12	Max. 80M/ line/ minute	13.5KW/ 6 Servo	M5.5 kw	18.5KW	0.6 Mpa 400ml / min	6.8x3.56x1.7	R-1.6x3.7x1.7 M-2.0x2.9x1.5 U-1.7x2.5x1.5	7400 / 9200
IN-LINE TYPE	STR-750Si -A21E	W 300~750 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	11KW/ 6 Servo	M3.5 kw	13KW	0.6 Mpa 400ml / min	5.1x2.66x1.7	R-1.6x2.7x1.7 M-2.0x1.8x1.5	4100 / 5000
	STR-1000Si -A21E	W 450~1000 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	12.5KW/ 6 Servo	M4.0 kw	15KW	0.6 Mpa 400ml / min	5.1x2.86x1.7	R-1.6x2.9x1.7 M-2.0x2.0x1.5	4600 / 5650
	STR-1250Si -A21E	W 600~1250 Roll max.220	220~2000 / 0.008~0.12	Max. 100M/ line/ minute	12.5KW/ 6 Servo	M4.5 kw	15.5KW	0.6 Mpa 400ml / min	5.1x3.06x1.7	R-1.6x3.1x1.7 M-2.0x2.2x1.5	5250 / 6600
	STR-1500Si -A21E	W 700~1500 Roll max.220	220~2500 / 0.010~0.12	Max. 90M/ line/ minute	13.5KW/ 6 Servo	M5.0 kw	17.5KW	0.6 Mpa 400ml / min	5.1x3.31x1.7	R-1.6x3.4x1.7 M-2.0x2.6x1.5	5900 / 7300
	STR-1750Si -A21E	W 850~1700 Roll max.220	220~2500 / 0.012~0.12	Max. 80M/ line/ minute	13.5KW/ 6 Servo	M5.5 kw	18KW	0.6 Mpa 400ml / min	5.1x3.56x1.7	R-1.6x3.7x1.7 M-2.0x2.9x1.5	6900 / 8100

### MACHINE FEATURE:

01. Products roll diameter can up to Max. 220mm.
02. Easy change the bag length and tension by touch screen digital setting.
03. Shuttle type Sealing and Perforation designed make fast speed and smoothly work, Tensionless sealing; Low noise running and easy change perforation knife designed.
04. Every knife can change the tooth knife pitch for user require.
05. Printing mark function possibility.(optional)
06. Heavy duty lifting auto-unwind with Edge Position Control of OFF-LINE type.
07. Automatic speed follow by in-feed dancing device of IN-LINE type.
08. Easy to operate and maintain full-featured surveillance system by HMI.
09. Easy change designed for different core size of automatic rewind machine.
10. Micro tension system for thin film(min. 8 micrometer) and very easy to tear.
11. Heavy duty film make possibly. The total thickness for bottom sealing up to 240micro.

ps.: For packing size--R=Rewind machine; S=Slit sealing device;  
M= Main sealing and perforation machine; U=Unwind device.